



US005987760A

**United States Patent** [19]  
**Hsu**

[11] **Patent Number:** **5,987,760**  
[45] **Date of Patent:** **Nov. 23, 1999**

[54] **CIRCLE DRAWING TOOL**

[75] **Inventor:** **Walter W. Hsu, Yinlin Hsien, Taiwan**

[73] **Assignee:** **Walter's Co., Ltd., Yonlin Hsien, Taiwan**

[21] **Appl. No.:** **08/993,992**

[22] **Filed:** **Dec. 18, 1997**

[51] **Int. Cl.** <sup>6</sup> ..... **B43L 9/00**

[52] **U.S. Cl.** ..... **33/27.03; 33/562**

[58] **Field of Search** ..... **33/27.03, 562, 33/555.1, 555.2**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

3,795,053	3/1974	Burke	33/27.03
4,129,948	12/1978	Hatter et al.	33/27.03
4,589,210	5/1986	Konrad	33/27.03
4,899,449	2/1990	Fouladian	33/27.03
5,125,161	6/1992	Guthrie	33/27.03
5,384,964	1/1995	McKay	33/27.03
5,390,418	2/1995	Buono et al.	33/27.03
5,615,485	4/1997	Stoneberg	33/562

**FOREIGN PATENT DOCUMENTS**

2806617	8/1978	Germany	33/27.03
3134890	3/1983	Germany	33/27.03
564645	10/1944	United Kingdom	33/27.03

*Primary Examiner*—Diego Gutierrez

*Assistant Examiner*—Quyen Doan

*Attorney, Agent, or Firm*—Browdy and Neimark

[57] **ABSTRACT**

An improved circle drawing tool is equipped with a doughnut-shaped outer board, a circular slide track mounted onto the outer board and an inner circular board provided with rolling balls in a plurality of receiving cavities thereof and having such a diameter that it can be rotarily engaged with the slide track as well as the doughnut-shaped outer board in assembly. On the doughnut shaped outer board are disposed a plurality of round holes distributed one by one consecutively according to their diameters. There are 4 straight lines separated apart at 90 degrees in angle. There are a number of small pen insertion holes consecutively spaced by 4 mm on each line and each starting point of the four lines is 1 mm farther away from the center of the outer board. There are 10 radial lines equally divided on the inner circular board. On each radial line there are a plurality of consecutive pen insertion holes defined thereon with every two neighboring points 10 mm spaced apart. Each starting point of all the 10 lines is 1 mm farther away consecutively from the center of the circular board so as to make the pen insertion holes distributed within a certain range in 1 mm divisional level. An extension arm having a plurality of pen insertion holes can be connected to the rotary outer board so as to permit circles larger than the diameter of the outer board can be drawn.

**3 Claims, 4 Drawing Sheets**

